



## High Capacity Control System – RPC-5000A

The RPC-5000A offers cooling capacities of 500 kW (1,700,000 BTUH), over a temperature range of +5°C to +40°C, and flow rates of up to 20 gallons per minute.

The standard features include:

- Unit is charged with Non-CFC refrigerants
- Automatic Alarm monitoring high temperatures, low reservoir level, flow rate, and compressor
- Internally mounted filter housing
- Water, electrical and other interface connections located on back panel for easy access
- Solid state temperature controller accurate to  $\pm 1^\circ\text{C}$  with a digital readout to display set point / actual temperature
- Corrosion-resistant steel frame with removable panels and casters



Model shown - RPC 1750

Front panel controls ensure ease of use and include:

- *Standard temperature gauge, supply pressure gauge, coolant flow meter, power switch*

Panel indicator lights monitor:

- *Pumping and cooling modes, temperature, pressure flow*

Options available for this model are: (AA2), (AA4) and (AA6) Alarm Options, (RSCA) and (RSAA) Serial Interfaces, (RS232) Service Interface, (RAA) Remote Control, (RE) Remote Control, (RTS) Remote Temperature Sensor, (MPIO) Multi-channel I/O, (RC) Split Package, (W) Water Cooled Condenser, (XRC) High Cap. Condenser, (DI) DI System, (CD) Cont. Deionization, (RM) Resistively Monitor, (MW) Automatic Fill System, (UV) Ultra Violet Unit, (SF) Special Fluids, (LT) Low Temperature, (HE) Heater, (WTR) Wide Temp. Range, (EMO) Safety Interlock, (CE) Safety Interlock, (ENV) Water Resist Enc, (DMD), (10GMD), and (20GMD) Magdrive Pumps, (20GHP), (40GHP) Bronze Pump and (60GHP) Bronze Pumps.

Flowrite© Model	RPC-5000A
Horsepower	150
Coolant Temperature Range	+5°C to +40°C
Stability of Temperature	$\pm 1^\circ\text{C}$
Cooling Capacity in kW / hr (1000 BTUH)	500 (1700)
Channels	Single <b>or</b> Multiple
Flow Rate	Available Upon Request
Pressure	20 - 80 PSI
Cooling Media	Water / Propylene Glycol
Reservoir Volume	As Required
Dimensions O.D. (WxDxH)	As Required
Power	208/230 VAC 60 Hz 3 Ph <b>or</b> 440/480 VAC 60 Hz 3 Ph

To submit a Request For Quotation (RFQ) online, please visit our website at [www.flowrite.com](http://www.flowrite.com).

For parts orders please call the factory direct (1-800-989-7008) or go to the **Parts & Supplies** page on our website.